

11. 17.00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

NCR Corporation Docket No. 8779

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of Inventor(s): Paul L. Sinclair

For: LOCKING DATA IN A DATABASE AFTER AN OPERATION HAS BEGUN

Enclosed are also:

- X 2 Sheet(s) of Drawings
X An assignment of the invention to NCR Corporation
 _____ A certified copy of an application

CLAIMS AS FILED

FOR	Number Filed		Number Extra		Rate		Basic Fee (\$710)
Total Claims	29	-20 =	9	X	\$ 18	=	\$ 162
Independent Claims	5	-3 =	2	X	\$ 80	=	\$ 160
Multiple Dependent Claims	0			X	\$270	=	\$ 0
Total Filing Fee =							\$ 1,032

- X Please charge the above filing fee to the account of NCR Corporation, Deposit Account
No. 14-0225.

Please have all communications concerning this application and the recorded Assignment
directed to:

John D. Cowart
Intellectual Property Section
Law Department
NCR Corporation
101 West Schantz, ECD-2
Dayton, Ohio 45479-0001

Our telephone number is: 858-485-4903

Respectfully



Attorney for: Paul L. Sinclair

CEPT, UNITED STATES PATENT AND TRADEMARK OFFICE
 "E" 11-16-00 EK29554241545
 Date of filing: 11-16-00
 This application is being deposited
 with the U.S. Patent and Trademark Office
 OFFICE 101 West Schantz, ECD-2
 the date in the above address in the Assistant
 Commissioner, Washington, D.C. 20231.
 Sallie Spicer
 (Typed or Printed Name)
 (Signature of Sallie Spicer)

UNITED STATES
PATENT APPLICATION

for

**LOCKING DATA IN A DATABASE AFTER AN
OPERATION HAS BEGUN**

submitted by

**Paul L. Sinclair
Albert Maghbouleh**

on behalf of

**NCR Corporation
Dayton, Ohio**

Express Mail No.: **EK295542415US**
Date: 11-16-00

Prepared by

John D. Cowart
Reg. 38,415
NCR Corporation
101 W. Schantz Avenue
Dayton, OH 45479
(858) 485-4903 [Voice]
(858) 485-2581 [Fax]

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

"EXPRESS MAIL" Mailing Label Number **EK29554241545**

Date of Deposit 11-16-00

I hereby certify that this paper or fee is being deposited with the United States Postal Service "EXPRESS MAIL POST OFFICE TO ADDRESSEE" Service under 37 CFR 1.10 on the date indicated above and is addressed in the Assistant Commissioner for Patents, Washington, D.C. 20231.

Sallie Spicer

(Typed or Printed Name of Person Mailing Paper or Fee)

Sallie Spicer
(Signature of Person Mailing Paper or Fee)

LOCKING DATA IN A DATABASE AFTER AN OPERATION HAS BEGUN

Background

Database systems are nearly ubiquitous in modern-day business operations. Most business concerns electronically store at least some sort of information about their operations, inventory, transactions, and customers in database systems. Many companies use very large database systems, commonly known as data warehouses, to better understand the various aspects of their businesses and thus gain competitive advantage over rival companies. Data warehousing systems typically include a complex network of information processing and storage subsystems, complete with analysis tools that help their owners make sense of the vast amounts of information stored in the systems.

In general, companies that use data warehousing systems perform hundreds and even thousands of data-analysis and data-manipulation operations, such as loading data into the databases and retrieving data through database queries, on those systems on a daily basis. These companies also perform routine maintenance or data-definition operations, such as organizing the data into tables and creating indices for these tables, many times per week. Historically, these maintenance operations have required exclusive access to portions of the database and thus have involved the use of locking procedures that prevent, for limited time periods, the execution of data-manipulation operations on the affected portions of the databases. In many data warehousing systems, the number and length of these maintenance operations is very substantial and thus significantly impacts the amount of time that the systems are available for data-manipulation operations. As a result, these maintenance operations are usually carried out in "off-hour" periods, typically in the late-night or early-morning hours.

As the amount of data stored in data warehousing systems and the numbers of concurrent users of those systems increase, the amount of time needed for performing data-manipulation operations is also increasing. Many companies now perform data-manipulation operations well into the off-hour periods during which maintenance operations traditionally have occurred. These companies quite frequently must choose

between completing certain data-manipulation operations and initiating maintenance operations that lock portions of the database.

Summary

Described below is a database management system that receives a request to perform an operation on a set of target data and, at some point after it begins executing that operation, places a lock on the target data to prevent concurrent execution of other operations on the target data. In some embodiments, the system receives an instruction from a user to perform a data-definition operation on a set of target data; places an initial lock on the target data at a level that allows at least one concurrent operation on the target data; begins executing the operation; and then places a final lock on the target data at a level that excludes all other concurrent operations on the target data.

Other features and advantages will become apparent from the description and claims that follow.

Brief Description of the Drawings

FIG. 1 is a block diagram of a database system having a massively parallel processing (MPP) architecture.

FIG. 2 is a flow chart of a technique for locking data in the database system after an operation targeting the data has begun.

Detailed Description

FIG. 1 shows a data warehousing system 100 that operates under control of a database-management system (DBMS) program. The DBMS program performs many types of maintenance operations that, in traditional DBMS designs, normally place exclusive locks on portions of the database as soon as those operations begin and maintain those locks throughout the operations. The DBMS program in this system 100 is designed to use less severe locks, or no locks at all, when these operations begin. The system upgrades these locks to exclusive locks when necessary to complete the operations. As a result, many of these maintenance operations can execute concurrently

with other operations, including data-analysis and data-manipulation operations, which previously could not take place while the maintenance operations were executing. This type of concurrent execution provides greater database accessibility. Allowing the database user to select the initial lock level for each operation provides even greater flexibility, giving the user greater control over system performance and accessibility.

The data warehousing system 100 includes one or more computing nodes $105_{1...N}$ that manage the storage and retrieval of data in one or more data storage facilities $110_{1...M}$. Each of the computing nodes $105_{1...N}$ is driven by a processing subsystem $115_{1...N}$ that includes one or more processing units, or CPUs. In general, all of the CPUs within a node share operating system and memory resources.

Within each node, the processing subsystem $115_{1...N}$ operates under the control of at least one instance $120_{1...N}$ of the DBMS program. In a data warehousing system built on a massively parallel processing (MPP) platform, the each node runs several instances of the DBMS program, each forming a virtual processor that is assigned to manage some subset of the data in the storage facilities. Each DBMS process manages the assigned data in the database and governs access to the data by performing a prescribed set of operations on the data. In general, a user initiates these operations by delivering instructions through a remote computer system, such as a mainframe 130 connected directly to the database system or a client system 135 connected through a network 140. The user typically enters the instructions using a prescribed database-query language, such as the Structured Query Language (SQL) put forth by the American National Standards Institute (ANSI).

The operations performed by the database-management system include data-definition operations and data-manipulation operations, such as locking tables in the database; creating modifying, and deleting table definitions; inserting, deleting, or modifying rows of data within the tables; and retrieving data from the definitions and the tables. Data-definition operations are defined by a data-definition language (DDL) and typically include operations such as CREATE TABLE, CREATE INDEX and DROP USER. Data-manipulation operations are defined by a data-manipulation language

(DML) and typically include operations such as INSERT, DELETE, UPDATE and SELECT.

In general, each of these operations requires the DBMS process to lock some portion of the data so that the data is not corrupted by another process as the operation is carried out. Locking the data also prevents other DBMS operations from retrieving invalid or corrupt data. The DBMS process can place any one of several types of locks on a block of data, each with a unique level of severity. EXCLUSIVE locks prevent any concurrent access on the locked data by any other DBMS operations and thus are the most severe locks. WRITE locks prevent all concurrent READ, WRITE and EXCLUSIVE locks on the locked data. READ locks prevent all concurrent WRITE and EXCLUSIVE locks. ACCESS locks, the least severe, prevent only concurrent EXCLUSIVE locks on the locked data. Table I below illustrates the effects of these four types of locks.

CURRENT LOCK	REQUESTED LOCK			
	ACCESS	READ	WRITE	EXCLUSIVE
NONE	Granted	Granted	Granted	Granted
ACCESS	Granted	Granted	Granted	Queued
READ	Granted	Granted	Queued	Queued
WRITE	Granted	Queued	Queued	Queued
EXCLUSIVE	Queued	Queued	Queued	Queued

TABLE I

Locking data inhibits system performance by slowing the processing of concurrent operations. Many operations in traditional databases lock data for the duration of the operations even when the potential for corrupting or invalidating the data exists only during some portion of the operation. For example, a traditional CREATE INDEX operation requires an EXCLUSIVE lock on an entire table for the duration of the operation. This prevents any other type of concurrent access to that table, including that which does not alter the table or the data in it, at any time during the operation.

The DBMS program of FIG. 1 improves system performance through increased concurrency by reducing the severity of the locks that certain operations initially place on the data. The DBMS program then upgrades these locks to more severe levels when necessary to complete the operations. For example, CREATE INDEX operations begin not with EXCLUSIVE locks on the affected table, but with less severe locks, such as WRITE locks or READ locks. The DBMS upgrades these locks to EXCLUSIVE locks when necessary to complete the CREATE INDEX operations – *i.e.*, after subtables are created but before the associated data dictionaries and table headers are modified. In some implementations, the DBMS program allows the database user to choose the initial lock levels for these operations.

Applying reduced-severity locks at the outset of data-definition operations allows a greater number of concurrent data-manipulation operations to occur while the data-definition operations are in progress, thus improving system throughput and, in turn, system performance. Below are some examples of the types of DDL statements that are subject to reduced-severity locks and the impact that these locks have on other operations.

A. COLLECT STATISTICS

In a typical database-management system, a COLLECT STATISTICS operation places a row-hash WRITE lock on certain blocks of data for the entire operation. The DBMS program of FIG. 1 delays this row-hash WRITE lock, placing no lock on the data, until after it has computed the requested statistics. Delaying the row-hash WRITE lock in this manner increases concurrency by allowing data-manipulation operations, such as SELECT, INSERT and DELETE operations, to occur on the target data over most of the time during which the COLLECT STATISTICS operation executes.

B. CREATE INDEX

Database-management systems normally place an EXCLUSIVE lock on a table upon initiating a CREATE INDEX operation for that table. The DBMS program of FIG. 1 replaces the initial EXCLUSIVE lock with a WRITE lock on the target table.

Alternatively, the DBMS process allows the user to specify an initial lock level (*e.g.*, a READ, ACCESS or SHARE lock) and places this type of lock on the table. The DBMS process then upgrades this reduced-severity lock to an EXCLUSIVE lock on the table after it creates the index subtables, but before it locks and modifies the corresponding data dictionary and before it modifies the table headers.

Beginning with a reduced-severity lock in this manner allows the CREATE INDEX statement to run concurrently with certain data-manipulation operations, such as a SELECT operation that places an ACCESS or READ lock on the table before the CREATE INDEX operation upgrades to an EXCLUSIVE lock. This also allows the CREATE INDEX operation to run concurrently on the table with other data-definition operations, such as a COLLECT STATISTICS operation, until one of the operations upgrades to an EXCLUSIVE lock. Because CREATE INDEX operations typically occur over relatively long periods of time, reducing the initial lock severity of these operations can produce significant improvements in system throughput.

C. ALTER TABLE . . ., FALLBACK

Database management systems normally place an EXCLUSIVE lock on an entire table upon initiating an ALTER TABLE . . ., FALLBACK operation on that table. The DBMS program of FIG. 1 instead places a WRITE lock on the table at the outset of this type of operation. Alternatively, the DBMS program uses some other reduced-severity lock specified by the database user.

As with the CREATE INDEX statement, beginning an ALTER TABLE . . ., FALLBACK statement with a reduced-severity lock allows the operation to run concurrently with certain data-manipulation operations, such as a SELECT operation, targeting the same table. The ALTER TABLE . . ., FALLBACK operation in this case can also run concurrently with other data-definition operations, such as a COLLECT STATISTICS operation, until one of the operations upgrades to an EXCLUSIVE lock.

D. MODIFY DATABASE/USER

For most MODIFY DATABASE/USER operations, the DBMS program replaces the traditional EXCLUSIVE lock on the targeted database/user with an ACCESS lock. In some implementations, the DBMS program also removes the row-hash WRITE lock that conventional database-management systems place on the database that is the immediate parent of the database or user targeted by the operation. For MODIFY DATABASE/USER operations in which the user specifies certain options, such as the "SPOOL," "TEMP" and "PERM" options, the DBMS program replaces a traditional table-level WRITE lock on the space-management table with two row-hash locks: (1) a READ lock (SPOOL or TEMP) or WRITE lock (PERM) on the space-management entry for the immediate parent of the targeted database/user, and (2) a WRITE lock on the space-management entry for the targeted database/user. This allows the MODIFY DATABASE/USER operation to run concurrently with almost all DML statements. A MODIFY DATABASE/USER statement for which the user has specified the "SPOOL," "TEMP" or "PERM" option can run concurrently with any DML statement that does not target the same database or user as the MODIFY statement.

Upon receiving an instruction to perform one of these operations on the database, the DBMS program determines both the initial and final locks associated with the operation. In those cases in which the user is allowed to specify the initial lock level, the DBMS program applies the lock specified by the user. Table II illustrates the effects for some of these operations.

OPERATION	INITIAL LOCK	FINAL LOCK
COLLECT STATISTICS	None or User-defined	WRITE on row-hash
CREATE INDEX	WRITE on table or User-defined (at least a READ lock)	EXCLUSIVE on table
ALTER TABLE...,FALLBACK	WRITE on table or User-defined (at least a READ lock)	EXCLUSIVE on table

TABLE II

FIG. 2 is a flow chart showing one technique for implementing reduced-severity locking in a database-management system. The system first receives an instruction from a user to perform a data-definition or data-manipulation operation on the database (step 200). In a typical database system, the user enters the instruction as a Structured Query Language (SQL) command through an interface program, such as a UNIX command-line interface. Upon receiving the instruction, the system determines whether any user-specified lock levels are included in the instruction (step 205). The system then determines the initial and final lock levels for the operation (step 210; see also Table II). If the operation is of a type that allows user-defined locking, the system replaces the initial lock specified in the table with that specified by the user (step 215).

After determining the initial and final lock levels, the system attempts to place the initial lock on the target data (step 220). If the data is already locked by another operation that prevents placement of the lock (see Table I), the system queues the current operation until the other operation is complete. When the system succeeds in placing the initial lock on the target data, it begins executing the operation on the locked data (step 225).

The system proceeds with execution until it reaches the point at which it must upgrade the lock severity to complete the operation (step 230). The system then attempts to upgrade to the more severe lock (step 235). If the system finds that another operation

has locked the data at a level that prevents the upgrade (see Table I), it queues the upgrade until the other operation is complete. If the attempted upgrade causes a deadlock condition (step 240), the system aborts the current operation and sends a message instructing the user to resubmit the operation (step 245), as described in more detail below. Upon successfully upgrading to the more severe lock (step 250), the system completes the operation (step 255) and then releases the lock on the target data (step 260).

Under some circumstances, applying a less severe lock at the outset of an operation might increase the chances of deadlock. For example, a deadlock might occur when a CREATE INDEX or ALTER TABLE operation begins with a WRITE lock on a table and executes concurrently with a data-manipulation operation using an ACCESS lock that will upgrade to a READ, WRITE or EXCLUSIVE lock on the same table. The likelihood that a deadlock actually will occur depends on the workload and transaction mix of a given database application. Overall, deadlock conditions occur very infrequently.

One way of handling deadlock conditions is aborting one of the operations (*e.g.*, the later-issued operation) and sending a message instructing the user to resubmit the aborted operation. Aborting operations in this manner to defuse deadlock conditions inhibits system performance, but the performance gains achieved through increased concurrency outweigh the effects of deadlock. Allowing the user to specify the initial lock level gives the user greater control over the affects of this performance tradeoff.

Computer-based and other implementations

The various implementations of the invention are realized in electronic hardware, computer software, or combinations of these technologies. Most implementations include one or more computer programs executed by a programmable computer. In general, the computer includes one or more processors, one or more data-storage components (*e.g.*, volatile and nonvolatile memory modules and persistent optical and magnetic storage devices, such as hard and floppy disk drives, CD-ROM drives, and magnetic tape drives),

one or more input devices (*e.g.*, mice and keyboards), and one or more output devices (*e.g.*, display consoles and printers).

The computer programs include executable code that is usually stored in a persistent storage medium and then copied into memory at run-time. The processor
5 executes the code by retrieving program instructions from memory in a prescribed order. When executing the program code, the computer receives data from the input and/or storage devices, performs operations on the data, and then delivers the resulting data to the output and/or storage devices.

The text above describes one or more specific embodiments of the broader
10 invention. The invention also is carried out in a variety of alternative embodiments and thus is not limited to those described here. Therefore, other embodiments are within the scope of the following claims.

Claims

We claim:

5 1. A method for use in managing data in a database system, comprising:
receiving a request to perform an operation on a set of target data;
initiating execution of the operation; and
at some point after execution has begun, placing a lock on the target data to prevent
concurrent execution of other operations on the target data.

10 2. The method of claim 1, comprising placing an initial lock on the target data at a
level that prevents concurrent execution of at least one operation and, at some point after
execution has begun, placing a final lock on the target data at a level that prevents
concurrent execution of a larger set of operations.

15 3. The method of claim 2, where the initial lock allows concurrent execution of
operations that involve reading the target data.

20 4. The method of claim 2, where the final lock prevents concurrent execution of all
operations on the target data.

5. The method of claim 2, further comprising allowing a user to specify the type of
lock initially placed on the data.

25 6. The method of claim 1, where the operation is one of the following types: a
COLLECT STATISTICS operation, a CREATE INDEX operation, and an ALTER
TABLE operation.

7. A database system comprising:
at least one storage device;
at least one computing node configured to deliver data to and retrieve data from the
storage device; and

5 a database-management component configured to:
receive a request to perform an operation on a set of target data;
initiate execution of the operation; and
at some point after execution as begun, place a lock on the target data to
prevent concurrent execution of other operations on the target data.

10 8. The system of claim 7, where the database-management system is configured to
place an initial lock on the target data at a level that prevents concurrent execution of at
least one operation and, at some point after execution has begun, placing a final lock on
the target data at a level that prevents concurrent execution of a larger set of operations.

15 9. The system of claim 8, where the initial lock allows concurrent execution of at
least one other operation on the target data.

20 10. The system of claim 8, where the subsequent lock prevents concurrent
execution of all other operations on the target data.

11. The system of claim 8, where the database-management system is configured to
allow a user to specify the type of lock initially placed on the data.

25 12. The system of claim 7, comprising multiple computing nodes and multiple
storage devices, where each storage node is configured to manage storage of data on at
least a subset of the storage devices.

13. The system of claim 12, where the database-management system is configured to place the lock on a block of data that is spread across more than one of the storage devices.

5 14. The system of claim 7, where the operation is one of the following types: a COLLECT STATISTICS operation, a CREATE INDEX operation, and an ALTER TABLE operation.

10 15. A computer program, stored on at least one computer-readable storage medium, for use in managing data in a database system, comprising executable instructions that, when executed by a computer, cause the computer to:

receive a request to perform an operation on a set of target data;

initiate execution of the operation; and

15 at some point after execution has begun, place a lock on the target data to prevent concurrent execution of other operations on the target data.

20 16. The program of claim 15, where the program causes the computer to place an initial lock on the target data at a level that prevents concurrent execution of at least one operation and, at some point after execution has begun, placing a final lock on the target data at a level that prevents concurrent execution of a larger set of operations.

17. The program of claim 16, where the initial lock allows concurrent execution of at least one other operation on the target data.

25 18. The program of claim 16, where the subsequent lock prevents concurrent execution of all other operations on the target data.

19. The program of claim 16, where the program causes the computer to allow a user to specify the type of lock initially placed on the data.

20. The program of claim 15, where the operation is one of the following types: a COLLECT STATISTICS operation, a CREATE INDEX operation, and an ALTER TABLE operation.

5 21. A method for use in managing data in a database system, comprising:
receiving an instruction from a user to perform a data-definition operation on a set
of target data;
placing an initial lock on the target data at a level that allows at least one concurrent
operation on the target data;
10 initiating execution of the operation; and
at some point after execution has begun, placing a final lock on the target data at a
level that excludes all other concurrent operations on the target data.

15 22. The method of claim 21, where the initial lock excludes at least some
concurrent operations on the target data.

23. The method of claim 21, further comprising allowing a user to select the level of
the initial lock.

20 24. The method of claim 21, where placing an initial lock on the target data includes
placing one of the following types of locks on the target data: an ACCESS lock; a READ
lock; and a WRITE lock.

25 25. The method of claim 21, where placing a final lock on the target data includes
placing an EXCLUSIVE lock on the target data.

26. The method of claim 21, where placing an initial lock on the target data includes
locking an entire table.

27. The method of claim 21, where receiving the instruction from the user includes receiving an instruction to perform one of the following operations: a CREATE INDEX operation, a COLLECT STATISTICS operation, and an ALTER TABLE operation.

5 28. A method for use in managing data in a database system, the method comprising:

receiving an instruction to perform a MODIFY DATABASE/USER operation on a set of target data;

initiating execution of the operation; and

10 at some point during execution of the operation, concurrently executing another operation on objects within the targeted database or user.

29. The method of claim 28, further comprising maintaining an ACCESS lock on the target database or user and no locks on the immediate parent of the targeted database or user during execution of the MODIFY DATABASE/USER operation.

15

Abstract

A database management system receives a request to perform an operation on a set of target data and, at some point after it begins executing that operation, places a lock on the target data to prevent concurrent execution of other operations on the target data. In some embodiments, the system receives an instruction from a user to perform a data-
5 definition operation on a set of target data; places an initial lock on the target data at a level that allows at least one concurrent operation on the target data; begins executing the operation; and then places a final lock on the target data at a level that excludes all other concurrent operations on the target data.

DOCKET 8779.00




FIG. 1




FIG. 2

United States Patent Application

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

LOCKING DATA IN A DATABASE AFTER AN OPERATION HAS BEGUN

and identified by NCR Corporation Docket No. 8779, the specification of which:

- a. ☒ is attached hereto
- b. ☐ was filed on _____ as United States Application Number or PCT International Application Number _____ and was amended on _____ (if applicable), which I have reviewed and for which I solicit a United States patent.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate or any PCT application having a filing date before that of the application on the basis of which priority is claimed:

FOREIGN APPLICATION(S), IF ANY, CLAIMING PRIORITY UNDER 35 USC § 119

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)
	None		

OTHER FOREIGN APPLICATION(S), IF ANY, FILED BEFORE THE PRIORITY APPLICATION(S)

COUNTRY	APPLICATION NUMBER	DATE OF FILING (day, month, year)	DATE OF ISSUE (day, month, year)
	None		

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or 365(c) of any PCT international application(s) designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

U.S. PARENT APPLICATION OR PCT PARENT NUMBER	DATE OF FILING (day, month, year)	STATUS (patented, pending, abandoned)
None		

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below:

U.S. PROVISIONAL APPLICATION NUMBER	DATE OF FILING (Day, Month, Year)
None	

And I hereby appoint:

Michael Chan of Dayton, Ohio, Registration No. 33,663,
John D. Cowart of San Diego, California, Registration No. 38,415,
Douglas S. Foote of Dayton, Ohio, Registration No. 31,013,
Paul W. Martin of Dayton, Ohio, Registration No. 34,870,
James M. Stover of Dayton, Ohio, Registration No. 32,759.

my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. I hereby expressly waive my right to revoke the Power of Attorney granted above. Address all telephone calls to John D. Cowart at telephone number 858-485-4903.

Address all correspondence to:

John D. Cowart
NCR Corporation
101 West Schantz, ECD-2
Dayton, Ohio 45479-0001.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of inventor Paul L. Sinclair
Inventor's signature Paul L. Sinclair Date: 11/13/00
Residence Manhattan Beach, CA 90266
Citizenship United States of America
Post Office Address 100 N. Sepulveda Blvd., El Segundo, CA 90245

Full name of inventor Albert Maghbouleh
Inventor's signature Albert Maghbouleh Date: 11-13-00
Residence Los Angeles, CA 90048
Citizenship United States of America
Post Office Address 100 N. Sepulveda Blvd., El Segundo, CA 90245